



# PSM08 Door Contact Sensor

The Z-Wave 500 Series Module adopted

Fits Your Home Decoration Style

Extremely low power consumption

Long Battery Life

Easy To Install

Preliminary

---



## SPECS

<b>Power</b>	Operating Voltage	3.0 V by CR123A
	Standby Current (Sleep Mode)	13 uA
	MCU Wake Up Current	33 mA
	Low Battery Voltage	2.6 V
<b>RF Range</b>	Z-Wave	Upto 40M indoor*
<b>Battery</b>	CR123A	1700 mA
<b>Battery Life</b>	CR123A	3 years
<b>Mechanical</b>	Detector Dimension	85(L) x 24 (W) x 22(H) mm
	Magnet Dimension	45(L) x 12(W) x 11(H) mm
<b>Environment</b>	Operation Temperature	0 ~ 40° C
	Humidity	85%RH max
<b>Sensitivity</b>	Magnetic Gap	2 mm

Note:\*40M depending on building materials and building structure

### **Application:**

Home Security  
Environment Monitoring  
Home Automation

**8F., No. 653-2, Zhongzheng Rd.,  
Xinzhuang Dist., New Taipei City  
24257, Taiwan**

[www.philio-tech.com](http://www.philio-tech.com)

**TEL:+886-2-2908 8952**